

7063

Acrylic Core Tape



Product Description

tesa® 7063 is an acrylic foam tape offering high bonding power, high stress dissipation and resistance to different temperatures and weather. With its very good adhesion and resistance against plasticizer migration, it is able to bond hard-to-bond materials and metals. Its acrylic core compensates for different thermal elongation of bonded parts. It also offers a high immediate tack and peel adhesion.



Available in black with blue filmic liner.

Main Applications

- Hard-to-bond materials
- Powder coated
- Bumper rails
- Air distributaries

Product Information

| | | | |
|-----------------------------------|---|----------------------------------|----------------------|
| Backing | Thickness (mil) | Adhesion to steel (oz/in) | Adhesive Type |
| Acrylic Foam | 32 | 274.1 | Acrylic |
| Operating Temp. Range (°F) | Short Term Temp. Resistance (°F) | Elongation at Break (%) | |
| ≤158 | 338 | 1000 | |

Application and Storage

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.