

# 4962

Premium Double Coated Non-Woven Tape



## Product Description

tesa® 4962 is a double coated tape with a non-woven backing and tackified acrylic adhesive offering high adhesion, excellent grabbing power and excellent temperature resistance.

Available in translucent with liner.



## Main Applications

- Mounting of plastic parts
- Bonding of heavy paper
- Lamination of textile, leather and foam parts

## Product Information

<b>Backing</b>	<b>Thickness (mil)</b>	<b>Adhesion to steel (oz/in)</b>	<b>Adhesive Type</b>
Tissue	6.3	109.6	Acrylic
<b>Operating Temp. Range (°F)</b>	<b>Short Term Temp. Resistance (°F)</b>	<b>Elongation at Break (%)</b>	<b>Tensile Strength (lb/in)</b>
≤176	392	3	4.6

## Application and Storage

Note: The physical and performance characteristics shown are averages obtained from tests performed according to ASTM and PSTC test methods. Matco can make no warranty of any kind as to the results of the adhesive product use. The information published here is representative of laboratory research on these products and is believed to be reliable. Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.